

APPLICATION
FOR
UNITED STATES LETTERS PATENT

TITLE: WAVELENGTH SELECTING MODULE AND
WAVELENGTH SELECTING APPARATUS

APPLICANT: YOSHIRO SATO AND MANABU TAKAMI

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EL485679998US

I hereby certify under 37 CFR §1.10 that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Commissioner for Patents, Washington, D.C. 20231.

Date of Deposit October 19, 2001

Signature

Typed or Printed Name of Person Signing Certificate

WAVELENGTH SELECTING MODULE AND
WAVELENGTH SELECTING APPARATUS

BACKGROUND OF THE INVENTION

5

The present invention relates to an optical device which is used in optical communications, such as wavelength multiplexing communications, and, more particularly, to a wavelength selecting module that selects a light signal
10 having a specific wavelength from a plurality of light signals having different center wavelengths and a wavelength selecting apparatus that selects one or more types of light signals from plural light signals.

Optical devices, such as an optical fiber and collimator lens, have been used in optical communication equipment. As optical communications become more popular, further miniaturization and larger scale integration of optical communication equipment become necessary. Further,
15 optical communications require a technique of selectively demultiplexing light by wavelength. In this respect, optical ~~filters have been proposed, such as an edge filter or a~~
20 narrow band filter (see Fig. 11), which is a multilayer filter having an alternate stack of dielectric layers with a high refractive index and dielectric layers with a low
25 refractive index.

A filter module 100 according to the related art of Fig. 11 selects a light signal having a specific wavelength from a
30 plurality of light signals having different center wavelengths (λ_1 to λ_n). The filter module 100 includes a two-core collimator 101, a single-core collimator 102, and a multilayer filter 103 provided between the collimators 101

and 102. The two-core collimator 101 includes a two-core capillary 104 which holds two optical fibers, and a collimator lens 105 comprising a rod lens. The single-core collimator 102 includes a single-core capillary 106 which
5 holds a single optical fiber, and a collimator lens 107. Reference numeral "108" denotes a sleeve. The filter module 100 passes only a light signal having a specific wavelength (e.g., λ_1) among the light signals having center wavelengths λ_1 to λ_n and reflects the remaining light signals having
10 center wavelengths λ_2 to λ_n .

The specific wavelength (λ_1) is determined in accordance with the wavelength selecting characteristic of the multilayer filter 103 and the filter module 100 always
15 selects a light signal which has the determined specific wavelength. In case of using the filter module 100, therefore, it is not possible to arbitrarily switch between selection of a light signal having a specific wavelength and non-selection of the light signal.

20

Fig. 12 is a schematic diagram of a wavelength selecting apparatus 200 which has a plurality of filter
modules 100A, 100B, 100C and so forth cascade-connected. In the wavelength selecting apparatus 200, the filter module
25 100A selects a light signal having a center wavelength λ_1 and reflects the other light signals (λ_2 to λ_n). The filter module 100B selects a light signal having a center wavelength λ_2 and reflects the other light signals (λ_3 to λ_n). The filter module 100C selects a light signal having a center
30 wavelength λ_3 and reflects the other light signals (λ_4 to λ_n). Likewise, the light signals that have the center wavelengths λ_4 , λ_5 , ... and λ_n are selected one after another.

The wavelength selecting apparatus 200 has the following disadvantages.

5 (a) Since light signals that have the center wavelengths $\lambda_1, \lambda_2, \lambda_3, \dots$ are always selected by plural (n) filter modules 100A, 100B, 100C, ..., respectively, it is not possible to arbitrary select more than one type of light signal from light signals of λ_1 to λ_n .

10

(b) Those light signals which have wavelengths not selected by each filter module are reflected and enter the next filter module. Therefore, a light signal loss occurs every time each filter module reflects light signals and such
15 losses are accumulated in accordance with the number of filter modules. Specifically, as the intensities of the light signals of λ_2 to λ_n fall through reflection by the filter module 100A, the intensity of the light signal of λ_2 that is selected by the filter module 100B is lower than the
20 intensity of the first light signal. Since the intensities of the light signals of λ_3 to λ_n become lower through

~~reflection by the filter module 100B, the intensity of the~~
light signal of λ_3 that is selected by the filter module 100C is lower than the intensity of the light signal of λ_2 .
25 Apparently, the intensity of a light signal becomes lower as the selection order of that light signal becomes later.

As the number of filter modules connected becomes larger, the light signal loss (the attenuation of the light
30 intensity) becomes greater. To prevent an increase in light signal loss, it is necessary to improve the connection of the individual filter modules. In case where the intensity of a

light signal becomes lower than demanded, the light signal should be amplified by an amplifier. The attempts to improve the connection of the individual filter modules or the use of an amplifier seriously stands in the way of constructing an optical communication system which deals with a vast amount of information.

SUMMARY OF THE INVENTION

10 Accordingly, a first object of the present invention is to provide a wavelength selecting module capable of switching between selection and non-selection of light having a specific wavelength.

15 A second object of the present invention is to provide a wavelength selecting apparatus which arbitrarily selects one or more types of light signals from plural types light signals having different center wavelengths and suppresses attenuation of the intensity of the selected light.

20 In a first aspect of the present invention, a ~~wavelength selecting module for selecting a light signal~~ having a specific wavelength from a plurality of light signals having different center wavelengths is provided. The plurality of light signals are provided as diverging light. The module includes a first collimator for collimating the diverging light to generate a collimated light beam and a liquid crystal cell having a predetermined helical direction. The liquid crystal cell separates a light signal having a specific wavelength among the plurality of light signals of the collimated light beam into a left circularly polarized light and a right circularly polarized light, reflects one of the left and right circularly polarized light signals that

has a same optical rotatory direction as the predetermined helical direction toward the first collimator in a first state, and passes the plurality of light signals of the collimated light beam in a second state. The liquid crystal cell changes between the first state and the second state in accordance with a change in physical energy applied thereto.

In a second aspect of the present invention, a wavelength selecting apparatus for selecting at least one light signal from a plurality of light signals having different center wavelengths is provided. The plurality of light signals are provided as diverging light. The apparatus includes a plurality of wavelength selecting modules and a plurality of optical fibers for optically connecting the plurality of wavelength selecting modules. Each wavelength selecting module includes a first collimator for collimating the diverging light to a generate a collimated light beam and a liquid crystal cell having a predetermined helical direction and receiving the plurality of light signals of collimated light beam from the first collimator. The liquid crystal cell separates a light signal having an associated wavelength among the plurality of light signals of the collimated light beam into a left circularly polarized light and a right circularly polarized light, reflects one of the left and right circularly polarized light signals that has a same optical rotatory direction as the predetermined helical direction toward the first collimator in a first state, passes the plurality of light signals of the collimated light beam in a second state. The liquid crystal cell changes between the first state and the second state in accordance with a change in physical energy applied thereto.

In a third aspect of the present invention, a

wavelength selecting apparatus for selecting at least one light signal from a plurality of light signals having different center wavelengths is provided. The plurality of light signals are provided as diverging light. The apparatus

5 includes a first collimator for collimating the diverging light to generate a collimated light beam and a liquid crystal cell unit for receiving the plurality of light signals of the collimated light beam from the first collimator and reflecting at least one light signal toward

10 the first collimator. The liquid crystal cell unit includes a plurality of stacked liquid crystal cells. Each liquid crystal cell includes a liquid crystal which has a pair of surfaces and a predetermined helical direction. The liquid crystal separates a light signal having an associated

15 wavelength among the plurality of light signals of the collimated light beam into a left circularly polarized light and a right circularly polarized light, reflects one of the left and right circularly polarized light signals that has a same optical rotatory direction as the predetermined helical

20 direction toward the first collimator in a first state, passes the plurality of light signals of the collimated light beam in a second state. The liquid crystal changes between

the first state and the second state in accordance with a change of a voltage applied thereto. Each liquid crystal

25 cell further includes a pair of transparent electrodes which is provided on the pair of surfaces of the liquid crystal and to which the voltage is applied. At least one liquid crystal enters the first state by individually changing voltages applied to the liquid crystals via the pairs of transparent

30 electrodes.

Other aspects and advantages of the invention will become apparent from the following description, taken in

conjunction with the accompanying drawings, illustrating by way of example the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

5

The invention, together with objects and advantages thereof, may best be understood by reference to the following description of the presently preferred embodiments together with the accompanying drawings in which:

10 Fig. 1 is a schematic diagram of a wavelength selecting module according to a first embodiment of the present invention;

Fig. 2 is a schematic diagram of a wavelength selecting module according to a second embodiment of the present
15 invention;

Fig. 3 is a schematic diagram of a wavelength selecting module according to a third embodiment of the present invention;

20 Fig. 4 is a schematic diagram of a wavelength selecting apparatus according to a fourth embodiment of the present invention;

Fig. 5 is a schematic diagram showing a part of the wavelength selecting apparatus of Fig. 4;

25 Fig. 6 is a schematic diagram of a wavelength selecting apparatus according to a fifth embodiment of the present invention;

Fig. 7 is a schematic diagram showing a part of the wavelength selecting apparatus of Fig. 6;

30 Fig. 8 is a schematic diagram of a wavelength selecting apparatus according to a sixth embodiment of the present invention;

Fig. 9 is a schematic diagram showing a part of the wavelength selecting apparatus of Fig. 8;

Fig. 10 is a graph showing the optical property of a cholesteric liquid crystal;

Fig. 11 is a schematic diagram of a filter module according to the prior art; and

5 Fig. 12 is a schematic diagram of a wavelength selecting apparatus according to the prior art.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

10 In the drawings, like numerals are used for like elements throughout.

(First embodiment)

A wavelength selecting module 21 according to a first
15 embodiment of the present invention will now be described with reference to Fig. 1. The wavelength selecting module 21 selects a light signal having a specific wavelength (e.g., λ_1) among a plurality of light signals (mixed light signals) having center wavelengths (λ_1 to λ_n). The wavelength
20 selecting module 21 has a liquid crystal cell (LC cell) 22, a collimator having two optical fibers (hereinafter referred as a two-core collimator) 23 arranged to face a first side (light-incident side) of the LC cell 22, a collimator having one optical fiber (hereinafter referred as a single-core
25 collimator) 24 arranged to face a second side (light-emerging side) of the LC cell 22, and a sleeve 25 for holding the LC cell 22 and the collimators 23 and 24. The sleeve may be replaced with a holding member, such as a casing.

30 The LC cell 22 has a cholesteric liquid crystal 26 and a pair of transparent electrodes 27 respectively provided on both surfaces of the cholesteric liquid crystal 26. The transparent electrodes 27 are respectively connected to a

pair of terminals 28. The terminals 28 are supplied with a voltage pulse signal whose ON/OFF state is controlled to enable or disable the voltage that is applied between the pair of transparent electrodes 27.

5

The cholesteric liquid crystal 26 has the "circular dichroism" to separate a light signal having a specific wavelength (λ_1) among plural light signals as a collimated light beam emitted from the two-core collimator 23 into two
10 circularly polarized light signals of right and left optical rotatory powers, and the "selective reflection effect" to selectively reflect that circularly polarized light signal of the light signal having the specific wavelength which has the same optical rotatory direction as the helical direction of
15 LC cell 22.

That is, the cholesteric liquid crystal 26 separates a light signal having a specific wavelength into right and left circularly polarized light signals in accordance with the
20 voltage applied to the pair of transparent electrodes 27, and changes between a first state (planar texture) of selectively reflecting that circularly polarized light signal which has the same optical rotatory direction as the helical direction and a second state (homeotropic texture) of passing a light
25 signal.

It is assumed that the optical rotatory direction of circularly polarized light is defined with respect to incident light and that the cholesteric liquid crystal 26 is
30 a right optical rotatory crystal which has a right helical direction. In this case, the left circularly polarized light that has the opposite optical rotatory direction to the helical direction is passed and the right circularly

polarized light that has the same optical rotatory direction as the helical direction is selectively scattered and reflected.

5 The maximum scattered reflection (selective light scattering) occurs at a wavelength λ_0 (the maximum selective light scattering wavelength λ_0 shown in Fig. 10) according to the following equation (1).

$$\lambda_0 = n \cdot p \quad (1)$$

10 where p is the helical pitch of the cholesteric liquid crystal 26 and n is an average refractive index in a plane perpendicular to the helical axis of the liquid crystal 26. The average refractive index n is given by the following equation (2).

15
$$n = \sqrt{\{ (n_{\parallel})^2 + (n_{\perp})^2 \}^{1/2} / 2} \quad (2)$$

The wavelength bandwidth $\Delta\lambda$ of the scattered reflected light is given by the following equation (3).

$$\Delta\lambda = \Delta n \cdot p \quad (3)$$

20 where $\Delta n = n_{\parallel} - n_{\perp}$.

According to the first embodiment, the average refractive index n and the helical pitch p are set such that the maximum selective light scattering wavelength λ_0 becomes,
25 for example, the specific wavelength λ_1 .

When a voltage is applied between the pair of transparent electrodes 27, for example, the cholesteric liquid crystal 26 passes all of the light signals. When the
30 voltage application stops, the cholesteric liquid crystal 26 reflects (causes the scattered reflection of) the right circularly polarized light of the light signal having the

specific wavelength (λ_1), which has the same optical rotatory direction as the helical direction.

The two-core collimator 23 includes a two-core
5 capillary 31 which holds two optical fibers 29 and 30, and a
collimator lens 32, such as a rod lens. The diverging light
that emitted from the optical fiber 29 is collimated by the
collimator lens 32 and a collimated light beam in turn
perpendicularly enters the LC cell 22. The light signal that
10 is reflected by the LC cell 22 passes through the collimator
lens 32, enters the optical fiber 30 and emerges from the
optical fiber 30 as a optically selected light signal.

The single-core collimator 24 includes a single-core
15 capillary 34 which holds one optical fiber 33, and a
collimator lens 35, such as a rod lens. The light beam that
passes through the LC cell 22 is converged by the collimator
lens 35 and a converged light beam in turn enters the optical
fiber 33.

20

The wavelength selecting module 21 of the first
embodiment has the following advantages

(1) When a voltage is applied to the pair of
transparent electrodes 27, the cholesteric liquid crystal 26
25 is in the second state. Suppose that, in the second state, a
collimated light beam collimated from light signals having
plural wavelengths (λ_1 to λ_n) by the collimator lens 32 enter
the LC cell 22 perpendicularly. The light beam pass through
the LC cell 22 and is converged by the collimator lens 35.
30 The converged light beam enters the optical fiber 33 and
emerges therefrom. That is, none of the wavelengths of the
light signals are selected in this case.

When application of the voltage to the pair of transparent electrodes 27 stops, the cholesteric liquid crystal 26 enters the first state. When light signals perpendicularly enters the LC cell 22 in the first state, the cholesteric liquid crystal 26 separates the light signal having the specific wavelength (λ_1) among the incident light beam into right and left circularly polarized light signals and selectively reflects the right circularly polarized light (having the wavelength λ_1) that has the same optical rotatory direction as the helical direction. The reflected light signal having the specific wavelength (λ_1) is converged by the collimator lens 32 and a converged light beam enters the optical fiber 30 and emerges therefrom. That is, The reflected light is converged and is coupled to the optical fiber 30.

The light signal that has a specific wavelength (for example, λ_1) is acquired by disabling the pulse signal to be applied to the pair of terminals 28, 28 and setting the voltage applied between the pair of transparent electrodes 27 to Zero (0). Therefore, the wavelength selecting module 21 can arbitrarily switch between selection and non-selection of a light signal having a specific wavelength, and can be used in a variety of applications as an optical communication optical device.

(2) By adequately setting the average refractive index n and the helical pitch p , the wavelength selecting module 21 which changes the wavelength of light to be reflected by the cholesteric liquid crystal 26 can be designed easily.

(3) The two-core collimator 23 is located facing the

light-incident side of the LC cell 22. Therefore, the light signal having a specific wavelength which is reflected by the cholesteric liquid crystal 26 is converted by the collimator lens 32 to a collimate light beam which is acquired from the optical fiber 30. This can ensure easy and high-efficient optical coupling to optical fibers, which facilitates the construction of an optical communication system.

(4) The single-core collimator 24 is located facing the light-emerging side of the LC cell 22. Therefore, the light beam that has passed the cholesteric liquid crystal 26 is converged and a converged light beam enters to the optical fiber 33. That is, light beam is converged and coupled to the optical fiber 33. the Therefore, light signals can easily be transmitted to an optical communication optical device of another wavelength selecting module or the like. This ensures easy and high-efficient optical coupling to optical fibers, which facilitates the construction of an optical communication system.

(Second embodiment)

A wavelength selecting module 21A according to a second embodiment of the present invention will now be described with reference to Fig. 2. The wavelength selecting module 21A has a pair of wave plates 40 and 41 respectively provided on the surfaces of the pair of transparent electrodes 27 of the LC cell 22. The wave plate 40 is located between the collimator lens 32 and the transparent electrode 27 that is located on the light-incident side of the LC cell 22. The wave plate 41 is located between the transparent electrode 27 that is located on the light-emerging side of the LC cell 22 and the collimator lens 35.

The wave plate 40 converts collimated light beam from the collimator lens 32 to a circularly polarized light signal that has the same optical rotatory direction as the helical direction of the cholesteric liquid crystal 26. Because the cholesteric liquid crystal 26 is a right optical rotatory crystal which has a right helical direction, the wave plate 40 converts the collimated light beam to right circularly polarized light in the second embodiment. The wave plate 41 returns the right circularly polarized light signal that passes through the cholesteric liquid crystal 26 to a non-polarized light signal.

The wavelength selecting module 21A of the second embodiment has the following advantages.

(1) In the first embodiment, the right circularly polarized light signal of the right and left circularly polarized light signals separated from the light signal having a specific wavelength (λ_1) is reflected by the LC cell 22. Therefore, the reflection efficiency of the selected light signal is about 50%.

In the second embodiment, by way of contrast, the collimated light beam converted to the right circularly polarized light by the wave plate 40 enters the LC cell 22. When the applied voltage is set to 0, therefore, the light signal having a specific wavelength (λ_1) converted to the right circularly polarized light is reflected by the LC cell 22. Therefore, the reflection efficiency of the selected light signal is approximately 100%.

(2) The light signal (right circularly polarized

light) with a specific wavelength (λ_1) that is reflected by the cholesteric liquid crystal 26 is converted back to a non-polarized light signal by the wave plate 40 and is emitted from the optical fiber 30. Therefore, another optical communication optical device which receives the light emerging from the optical fiber 30 does not need to convert the circularly polarized light to a non-polarized light using a wave plate or the like. This ensures easy and high-efficient optical coupling to optical fibers, thereby facilitating the construction of an optical communication system.

(Third embodiment)

A wavelength selecting module 21B according to a third embodiment of the present invention will now be described with reference to Fig. 3. The wavelength selecting module 21B has a single-core collimator 51 arranged obliquely below with respect to the light-incident side of the LC cell 22, a single-core collimator 50 arranged obliquely above with respect to the light-incident side of the LC cell 22, and a single-core collimator 52 arranged obliquely above with respect to the light-emerging side of the LC cell 22. The single-core collimator 51 collimate a light beam to generate a collimated light beam and causes the collimated light beam to enter the LC cell 22 askew. The single-core collimator 50 converges a optically selected signal with a specific wavelength reflected by the LC cell 22 and emits the optically selected light signal. The single-core collimator 52 converges a light beam which passes the cholesteric liquid crystal 26 askew and emits the light beam.

The single-core collimator 50 includes a single-core capillary 54 for holding a single optical fiber 53, and a

collimator lens 55. The single-core collimator 51 includes a single-core capillary 57 for holding a single optical fiber 56, and a collimator lens 58. The single-core collimator 52 includes a single-core capillary 60 for holding a single
5 optical fiber 59, and a collimator lens 61.

The wavelength selecting module 21B of the third embodiment has the following advantages.

Two single-core collimators 50 and 51 are arranged on
10 the light-incident side of the LC cell 22. The adjustment (alignment) of the optical fiber 53 and the collimator lens 55 and the adjustment (alignment) of the optical fiber 56 and the collimator lens 58 are easier than the adjustment of the optical fibers and the collimator lenses of the two single-
15 core collimators 50 and 51. This facilitates the manufacture of the wavelength selecting module 21B.

(Fourth embodiment)

A wavelength selecting apparatus 300 according to a
20 fourth embodiment of the present invention will now be described with reference to Figs. 4 and 5.

The wavelength selecting apparatus 300 has plural (four in this embodiment) wavelength selecting modules M1 to M4
25 each having the same structure as that of the wavelength selecting module 21A of Fig. 2. The wavelength selecting apparatus 300 selects one or more types of light signal from plural light signals which have different center wavelengths (λ_1 to λ_4).

30

The four wavelength selecting modules M1 to M4 are cascade-connected via three optical fibers 65, 66 and 67. The four wavelength selecting modules M1 to M4 respectively

select light signals which have different wavelengths.

That is, the four wavelength selecting modules M1 to M4 are designed such that by adequately setting the average refractive indexes n and the helical pitches p of the cholesteric liquid crystals 26 of the four LC cells 22 (LC1 to LC4), light signals which have different wavelengths are respectively reflected by the four cholesteric liquid crystals 26. In the fourth embodiment, light signals of wavelengths λ_1 , λ_2 , λ_3 and λ_4 are respectively reflected and selected by the cholesteric liquid crystals 26 of the wavelength selecting modules M1, M2, M3 and M4.

As shown in Fig. 5, the wavelength selecting apparatus 300 has a controller 70 connected to the four wavelength selecting modules M1, M2, M3 and M4. The controller 70 controls the enablement and disablement of the pulse signal that is supplied to a pair of terminals 28 of each module. The four wavelength selecting modules M1, M2, M3 and M4 are retained in a single case 68 to provide the single modulated wavelength selecting apparatus 300.

The wavelength selecting apparatus 300 of the fourth embodiment has the following advantages.

25

(1) In case of selecting only one type of light signal (e.g., a light signal of the wavelength λ_1), the controller 70 disables the pulse signal that is supplied to the pair of terminals 28 of the wavelength selecting module M1 to thereby set the voltage that is applied to the pair of transparent electrodes 27 of the module M1 to 0 V. The pulse signals are supplied to the pairs of terminals 28 of the other wavelength selecting modules M2 to M4. In this case, the cholesteric

liquid crystal 26 of the wavelength selecting module M1 alone is in the first state. Therefore, the cholesteric liquid crystal 26 of the wavelength selecting module M1 reflects the light signal of the wavelength λ_1 among the light signals (λ_1 to λ_4) which have been converted to right circularly polarized lights by the wave plate 40. The reflected light signal is converted back to a non-polarized light signal by the wave plate 40. The non-polarized light signal is converted by the collimator 23 to a collimated light beam, which in turn emerges from the optical fiber 30.

In case of simultaneously selecting two or more types of light signals having different wavelengths (e.g., light signals of the wavelengths λ_1 and λ_2), the controller 70 disables the pulse signals that are supplied to the wavelength selecting modules M1 and M2 and allows pulse signals to be supplied to the other wavelength selecting modules M3 and M4. In this case, the cholesteric liquid crystals 26 of the wavelength selecting modules M1 and M2 are in the first state. Therefore, the cholesteric liquid crystals 26 of the wavelength selecting modules M1 and M2

and λ_2 . The reflected light signals are converted back to non-polarized light signals by the respective wave plates 40. As a result, collimated light beams of the wavelengths λ_1 and λ_2 are emitted from the modules M1 and M2, respectively.

In case of selecting only the light signal of the wavelength λ_3 , the controller 70 disables the pulse signal that is supplied to the wavelength selecting module M3. In this case, the cholesteric liquid crystal 26 of the wavelength selecting module M3 alone is in the first state.

Therefore, the cholesteric liquid crystal 26 of the wavelength selecting module M3 reflects the light signal of the wavelength λ_3 and a collimated light beam is emitted from the module M3.

5

In short, by controlling the pulse signal supplied to each wavelength selecting module (the voltage to be applied to the transparent electrodes), one or more types of light signal can be arbitrarily selected from a plurality of light signals which have different center wavelengths (λ_1 to λ_4).

10

(2) According to the prior art shown in Fig. 12, as the number of filter modules connected increases, the loss of a light signal increases (the light intensity attenuates).

15

According to the fourth embodiment, by way of contrast, while there is a slight reflection loss at the cholesteric liquid crystal 26 with respect to the light signal with the wavelength that is selected by any one of the wavelength selecting modules M1 to M4, there is no loss with respect to the light signals with unselected wavelengths. That is, the

20

wavelength selecting modules that do not correspond to the selected wavelength, without a loss, until it reaches the cholesteric liquid crystal 26 of the wavelength selecting module that corresponds to the selected wavelength. While the light signal reaches the corresponding module, therefore, the intensity of that light signal does not attenuate.

25

In case where the light signal of the wavelength λ_1 is selected by the wavelength selecting module M1, for example, the light signals of the wavelengths λ_2 to λ_4 pass the

30

cholesteric liquid crystal 26 of the module M1 without a loss and reach the respective modules M2 to M4. This suppresses the attenuation of the light signal intensity. It is therefore possible to connect a plurality of wavelength
5 selecting modules to increase the types of selectable wavelengths. This is particularly useful for large-scale optical communication systems which handle a vast amount of information.

10 (3) Each of the wavelength selecting modules M1 to M4 has the wave plates 40 and 41. Therefore, the reflection efficiency of the light signal selected by each of the modules M1 to M4 is approximately 100%. This further suppresses the loss of a light signal, which is more useful
15 for large-scale optical communication systems.

(Fifth embodiment)

A wavelength selecting apparatus 400 according to a fifth embodiment of the present invention will now be
20 described with reference to Figs. 6 and 7. The wavelength selecting apparatus 400 has plural (four) wavelength selecting modules M1 to M4 each having the same structure as that of the wavelength selecting module 21 of Fig. 1. The wavelength selecting apparatus 400 selects one type of light
25 signal or more from plural light signals which have different center wavelengths (λ_1 to λ_4). According to the fifth embodiment, because each of the wavelength selecting modules M1 to M4 does not have a wave plate, the number of components decreases, leading to cost reduction of the apparatus.

30

(Sixth embodiment)

A wavelength selecting apparatus 500 according to a sixth embodiment of the present invention will now be

described with reference to Figs. 8 and 9. The wavelength selecting apparatus 500 selects one or more types of light signals from plural light signals which have different center wavelengths (λ_1 to λ_4).

5

As shown in Fig. 9, the wavelength selecting apparatus 500 has a single-core collimator 80 on the light-incident side, a single-core collimator 81 on the light-emerging side and an LC cell unit 82 located between the collimators 80 and 81. The LC cell unit 82 selectively reflects one or more types of light signal from collimated light beam emerging from the single-core collimator 80. The wave plates 40 and 41 are respectively provided on the light-incident side and light-emerging side of the LC cell unit 82. The wavelength selecting apparatus 500 further has the sleeve 25, which holds the collimator lenses 80 and 81, the LC cell unit 82 and the wave plates 40 and 41. As shown in Fig. 8, the wavelength selecting apparatus 500 is connected to an optical circulator 84 via a single optical fiber 83.

20

As shown in Fig. 9, the single-core collimator 80 includes a single-core capillary 85 which holds the single optical fiber 83 connected to the optical circulator 84, and a collimator lens 86, such as a rod lens. The single-core collimator 81 includes a single-core capillary 88 which holds a single optical fiber 87, and a collimator lens 89, such as a rod lens.

25

The LC cell unit 82 includes plural sets (four sets) of LC cells 22 (LC1 to LC4). Each LC cell 22 includes the cholesteric liquid crystal 26 and the pair of transparent electrodes 27 provided on the respective surfaces of the liquid crystal 26. In the first state, the four sets of LC

30

cells 22 respectively reflect light signals having specific wavelengths different from one another. For example, the LC cells LC1, LC2, LC3 and LC4 respectively reflect light signals of wavelengths λ_1 , λ_2 , λ_3 and λ_4 in the first state.

5 That is, the LC cells LC1, LC2, LC3 and LC4 are designed such that their maximum selective light scattering wavelengths λ_0 respectively become the wavelengths λ_1 , λ_2 , λ_3 and λ_4 . When voltages applied to the transparent electrodes 27 of the LC cells LC1, LC2, LC3 and LC4 are changed (enabled or disabled),
10 the cholesteric liquid crystal 26 of at least one of the LC cells LC1, LC2, LC3 and LC4 changes between the first state and the second state.

According to the sixth embodiment, with a voltage
15 applied to the transparent electrodes of each of the LC cells LC1, LC2, LC3 and LC4, the cholesteric liquid crystal 26 of that LC cell is in the second state. When application of the voltage stops, the cholesteric liquid crystal 26 goes into the first state. In case where at least one of the
20 wavelengths λ_1 to λ_4 is selected, therefore, the voltage applied to the transparent electrodes 27 of at least one of
~~the LC cells LC1, LC2, LC3 and LC4 that corresponds to the selected~~
selected at least one of the wavelengths λ_1 to λ_4 is set to 0 V.

25

The optical circulator 84 receives the light signal sent from the light source or another optical communication optical device at a first terminal 84a and emits the light signal from a second terminal 84b to the single-core
30 collimator 80 via the optical fiber 83. Further, the optical circulator 84 receives the collimated light beam emerging from the single-core collimator 80 at the second terminal 84b

via the optical fiber 83 and emits the collimated light beam to an unillustrated light-receiving unit or another optical communication optical device from a third terminal 84c.

5 The wavelength selecting apparatus 500 of the sixth embodiment has the following advantages.

 (1) In case of selecting only one type of light signal (e.g., a light signal of the wavelength λ_2), the controller 70 disables the pulse signal supplied to the LC cell LC2.
10 Accordingly, the cholesteric liquid crystal 26 of the LC cell LC2 alone goes into the first state, and the cholesteric liquid crystal 26 of the LC cell LC2 reflects the light signal of the wavelength λ_2 among the light signals (λ_1 to λ_4) which have been converted to right circularly polarized
15 lights by the wave plate 40. The reflected light is converted back to a non-polarized light signal by the wave plate 40. The non-polarized light signal is converged by the collimator lens 86 and a light beam is in turn emitted to the optical circulator 84 via the optical fiber 83.

20

 In case of simultaneously selecting two or more types of light signals (e.g., light signals of the wavelengths λ_1 and λ_2), the controller 70 disables the pulse signals supplied to the LC cells LC1 and LC2 and allows pulse signals
25 to be supplied to the other LC cells LC3 and LC4. Accordingly, the cholesteric liquid crystals 26 of the LC cells LC1 and LC2 go into the first state, and the cholesteric liquid crystals 26 of the LC cells LC1 and LC2 respectively reflect the light signals of the wavelengths λ_1
30 and λ_2 . Those reflected light are converted back to non-polarized light signals by the respective wave plates 40. The light signals are converged and a light beam are in turn

emitted to the optical circulator 84 via the optical fiber 83.

In case of selecting only the light signal of the wavelength λ_3 , the controller 70 disables the pulse signal supplied to the LC cell LC3. This causes the cholesteric liquid crystal 26 of the LC cell LC3 alone to go into the first state. Therefore, the light signal having the wavelength λ_3 is reflected by the cholesteric liquid crystal 26 of the LC cell LC3. The reflected light is converted back to a non-polarized light signal by the wave plate 40, and a light beam is emitted to the optical circulator 84 via the optical fiber 83.

As apparent from the above, by controlling the voltage applied to the transparent electrodes 27 of each of the LC cells LC1 to LC4, one or more types of light signal can be arbitrarily selected from a plurality of light signals which have different center wavelengths (λ_1 to λ_4).

(2) Because the wave plates 40 and 41 are respectively provided on the light-incident side and the light-emerging

side of the LC cell, the right circularly polarized light is reflected by the cholesteric liquid crystal 26 of a corresponding one of the LC cells LC1 to LC4. Therefore, the reflection efficiency of the light signal selected by each of the LC cells LC1 to LC4 is approximately 100%. Further, even if the number of LC cells increases, the number of the wave plates 40 and 41 does not change. Therefore, the loss of the light signal that is selected by each LC cell is restrained and a large-scale optical communication system is constructed with fewer components.

(3) The LC cell unit 82 is provided between the single-core collimators 80 and 81. That is, two collimators have only to be provided on the light-incident side and the light-emerging side of the LC cell unit 82, respectively. Even if the number of LC cells increases, therefore, the number of the collimators need not be increased. This results in a reduction in the number of components and a reduction in manufacturing cost, and makes the wavelength selecting apparatus compact.

(4) The optical circulator 84 is connected to the wavelength selecting apparatus by the single optical fiber 83. Therefore, the single-core collimator 80, not a two-core collimator, has only to be provided on the light-incident side of the LC cell unit 82. This facilitates the alignment of the single-core collimator 80 on the light-incident side with the single-core collimator 81 on the light-emerging side and simplifies the structure of the wavelength selecting apparatus 500.

It should be apparent to those skilled in the art that the present invention may be embodied in many other specific forms without departing from the spirit or scope of the invention. Particularly, it should be understood that the invention may be embodied in the following forms.

(I) According to each embodiment discussed above, while the voltage is applied to the transparent electrodes 27 of the LC cell 22, the LC cell 22 is in the second state, and when the voltage application stops, the LC cell 22 shifts to the first state and reflect a light signal with a specific wavelength. A modification may be made such that while no

voltage is applied to the transparent electrodes 27 of the LC cell 22, the LC cell 22 is in the second state and when a voltage is applied to the transparent electrodes, the LC cell 22 shifts to the first state.

5

(II) According to each of the embodiments, as the voltage to be applied to the transparent electrodes 27 of the LC cell 22 is changed, the LC cell 22 is changed between the first state and the second state. The LC cell 22 may be
10 changed between the two states by changing the other physical energies than the voltage that are to be applied to the LC cell 22. The physical energies include, for example, heat, a magnetic field and force.

15 (III) Instead of the cholesteric liquid crystal, a chiral nematic liquid crystal which has an optical characteristic similar to that of the cholesteric liquid crystal may be used for the LC cell 22.

20 (IV) Instead of the cholesteric liquid crystal 26 that has right optical rotatory power, a left optical rotatory liquid crystal of which has a leftward helical direction may
be used.

25 (V) The number of wavelength selecting modules in Figs. 4 and 6 is not limited to four, but may be two or greater.

(VI) The number of the LC cells in the LC cell unit 82
30 in Figs. 8 and 9 is not limited to four, but may be two or greater.

Therefore, the present examples and embodiments are to be considered as illustrative and not restrictive and the

1. 1. The first part of the report
 2. 2. The second part of the report
 3. 3. The third part of the report
 4. 4. The fourth part of the report
 5. 5. The fifth part of the report
 6. 6. The sixth part of the report
 7. 7. The seventh part of the report
 8. 8. The eighth part of the report
 9. 9. The ninth part of the report
 10. 10. The tenth part of the report
 11. 11. The eleventh part of the report
 12. 12. The twelfth part of the report
 13. 13. The thirteenth part of the report
 14. 14. The fourteenth part of the report
 15. 15. The fifteenth part of the report
 16. 16. The sixteenth part of the report
 17. 17. The seventeenth part of the report
 18. 18. The eighteenth part of the report
 19. 19. The nineteenth part of the report
 20. 20. The twentieth part of the report
 21. 21. The twenty-first part of the report
 22. 22. The twenty-second part of the report
 23. 23. The twenty-third part of the report
 24. 24. The twenty-fourth part of the report
 25. 25. The twenty-fifth part of the report
 26. 26. The twenty-sixth part of the report
 27. 27. The twenty-seventh part of the report
 28. 28. The twenty-eighth part of the report
 29. 29. The twenty-ninth part of the report
 30. 30. The thirtieth part of the report
 31. 31. The thirty-first part of the report
 32. 32. The thirty-second part of the report
 33. 33. The thirty-third part of the report
 34. 34. The thirty-fourth part of the report
 35. 35. The thirty-fifth part of the report
 36. 36. The thirty-sixth part of the report
 37. 37. The thirty-seventh part of the report
 38. 38. The thirty-eighth part of the report
 39. 39. The thirty-ninth part of the report
 40. 40. The fortieth part of the report
 41. 41. The forty-first part of the report
 42. 42. The forty-second part of the report
 43. 43. The forty-third part of the report
 44. 44. The forty-fourth part of the report
 45. 45. The forty-fifth part of the report
 46. 46. The forty-sixth part of the report
 47. 47. The forty-seventh part of the report
 48. 48. The forty-eighth part of the report
 49. 49. The forty-ninth part of the report
 50. 50. The fiftieth part of the report
 51. 51. The fifty-first part of the report
 52. 52. The fifty-second part of the report
 53. 53. The fifty-third part of the report
 54. 54. The fifty-fourth part of the report
 55. 55. The fifty-fifth part of the report
 56. 56. The fifty-sixth part of the report
 57. 57. The fifty-seventh part of the report
 58. 58. The fifty-eighth part of the report
 59. 59. The fifty-ninth part of the report
 60. 60. The sixtieth part of the report
 61. 61. The sixty-first part of the report
 62. 62. The sixty-second part of the report
 63. 63. The sixty-third part of the report
 64. 64. The sixty-fourth part of the report
 65. 65. The sixty-fifth part of the report
 66. 66. The sixty-sixth part of the report
 67. 67. The sixty-seventh part of the report
 68. 68. The sixty-eighth part of the report
 69. 69. The sixty-ninth part of the report
 70. 70. The seventieth part of the report
 71. 71. The seventy-first part of the report
 72. 72. The seventy-second part of the report
 73. 73. The seventy-third part of the report
 74. 74. The seventy-fourth part of the report
 75. 75. The seventy-fifth part of the report
 76. 76. The seventy-sixth part of the report
 77. 77. The seventy-seventh part of the report
 78. 78. The seventy-eighth part of the report
 79. 79. The seventy-ninth part of the report
 80. 80. The eightieth part of the report
 81. 81. The eighty-first part of the report
 82. 82. The eighty-second part of the report
 83. 83. The eighty-third part of the report
 84. 84. The eighty-fourth part of the report
 85. 85. The eighty-fifth part of the report
 86. 86. The eighty-sixth part of the report
 87. 87. The eighty-seventh part of the report
 88. 88. The eighty-eighth part of the report
 89. 89. The eighty-ninth part of the report
 90. 90. The ninetieth part of the report
 91. 91. The ninety-first part of the report
 92. 92. The ninety-second part of the report
 93. 93. The ninety-third part of the report
 94. 94. The ninety-fourth part of the report
 95. 95. The ninety-fifth part of the report
 96. 96. The ninety-sixth part of the report
 97. 97. The ninety-seventh part of the report
 98. 98. The ninety-eighth part of the report
 99. 99. The ninety-ninth part of the report
 100. 100. The hundredth part of the report